

Symantec™ Gateway Security 320, 360, 360R

Powerful firewall protection for the small business network

The Symantec™ Gateway Security 300 Series is *the* high-performance, low-maintenance network appliance for small businesses. It combines a state-of-the-art firewall, a reliable Internet gateway, and a secure wireless option—all in one affordable solution. With simplified installation, embedded licensing, and easy-to-manage features like Symantec LiveUpdate,™ the 300 Series offers secure, high-speed connectivity with minimal overhead.

Ideal for your small businesses

Small business networks have big-time security needs. Yet, small businesses don't have the resources to spend on expensive, high-maintenance network solutions. That's why Symantec developed the Symantec Gateway Security 300 Series. This easy-to-manage appliance will get your network up and running quickly and easily, providing dependable connectivity and powerful protection.

Secure, reliable, and easy to manage

The appliance includes six security technologies—a stateful inspection firewall, secure IPsec VPN connectivity, intrusion detection, intrusion protection, content filtering, and policy enforcement for most Symantec connected clients. The network component is also multi-functional. It supports LAN switching, reliable Internet sharing, routing, and redundancy, along with an optional secure wireless LAN access point. An intuitive installation wizard and browser-based management interface make setup a breeze.

Ready to use and easy to keep up to date

The appliance comes with all the software you need to get started, while embedded licensing eliminates the hassle of license management and the cost of monthly subscription charges. Going forward, LiveUpdate keeps your firmware up to date, and to get you up and running smoothly, Symantec includes 90 days of world-class support.

At-a-glance

- Affordable, high-performance technology
- Easy installation
- Low maintenance
- Secure wireless capability

Features

- Six-in-one gateway security package
- Stateful inspection firewall
- Secure, high-performance gateway to gateway VPN
- Antivirus policy enforcement for most Symantec connected clients
- Intrusion detection
- Intrusion prevention
- Internet content filtering
- Fast, high-capacity Internet gateway with one WAN port (Dual WAN ports with bandwidth aggregation and load balancing available on 360/360R models)
- 4-port 10/100 LAN Switch (8-port 10/100 LAN Switch available on 360/360R models)
- Secure wireless LAN option



Model	320	360	360R
Features			
Maximum Rec. Nodes	50	100	100
Stateful Throughput	55Mbps	60Mbps	60Mbps
High-Availability Type	A/A, A/P, LB (A/A-Active/Active; A/P-Active/Passive; L/B-Load Balancing)	A/A, A/P, LB (A/A-Active/Active; A/P-Active/Passive; L/B-Load Balancing)	A/A, A/P, LB (A/A-Active/Active; A/P-Active/Passive; L/B-Load Balancing)
VPN 3DES Encryption	10Mbps	15Mbps	15Mbps
VPN AES Encryption	TBD	TBD	TBD
Memory	64MB	64MB	64MB
10/100 Ethernet Ports	1 WAN/4 LAN	2 WAN/8 LAN	2 WAN/8 LAN
Wireless LAN Option Slot Accepts	802.11b/g option	802.11b/g option	802.11b/g option
Connections Per Second	TBD	TBD	TBD
Concurrent Connections	10,000	10,000	10,000
VPN Clients	Optional	Optional	10 node included
Physical and Operational Specifications			
Operating Environment	0°C to 40°C; 32°F to 104°F; 10% to 80% relative humidity, non-condensing	0°C to 40°C; 32°F to 104°F; 10% to 80% relative humidity, non-condensing	0°C to 40°C; 32°F to 104°F; 10% to 80% relative humidity, non-condensing
Non-Operating Environment	-40°C to 65°C; -40°F to 149°F; 95% relative humidity, non-condensing	-40°C to 65°C; -40°F to 149°F; 95% relative humidity, non-condensing	-40°C to 65°C; -40°F to 149°F; 95% relative humidity, non-condensing
Operating Altitude	TBD	TBD	TBD
Safety	UL/cUL, CSA, TUV, CB	UL/cUL, CSA, TUV, CB	UL/cUL, CSA, TUV, CB
Emissions	FCC, CE, VCCI, MoC, ACA, SASO (IEC), SASB (IEC)	FCC, CE, VCCI, MoC, ACA, SASO (IEC), SASB (IEC)	FCC, CE, VCCI, MoC, ACA, SASO (IEC), SASB (IEC)
Immunity	TBD	TBD	TBD
Height	1.31 in/3.3 cm	1.31 in/3.3 cm	1.31 in/3.3 cm
Width	12 in/30.4 cm	12 in/30.4 cm	12 in/30.4 cm
Depth	5.9 in/15 cm	5.9 in/15 cm	5.9 in/15 cm
Weight	3 lbs/1.35 kg	3 lbs/1.35 kg	3 lbs/1.35 kg
Enclosure	Desktop	Desktop	Desktop
Support			
Silver Support	Unlimited calls for first 90 days during business hours	Unlimited calls for first 90 days during business hours	Unlimited calls for first 90 days during business hours
Gold Maintenance	Support after the first 90 days may be extended with Gold Maintenance providing business hour telephone support plus a 1 year extension of warranty and advanced warranty replacement. Available in one or two year terms.		
Platinum Support Uplift	Support after the first 90 days may be extended with Platinum Support Uplift providing 24x7 telephone support plus a 1 year extension of warranty and advanced warranty replacement. Available in one or two year terms.		
Warranty	1 year upon purchase	1 year upon purchase	1 year upon purchase

Symantec Corporation
World Headquarters
20330 Stevens Creek Blvd.
Cupertino, CA 95014 USA
1 408 517 8000
1 800 721 3934
www.symantec.com

.....
Symantec has worldwide operations in 38 countries. For specific country offices and contact numbers please visit our Web site.

Any system that runs Microsoft™ Internet Explorer 6.0 or higher or Netscape™ Navigator 7.0 or higher can be used to manage the Symantec Gateway Security 300 Series.